



# PROVEN PERFORMER

## Vended Stack Tumble Dryers

**STT30, STT45** (Gas Heat Standard)

### Features

- Double capacity in same floor space
- Extra large cylinder capacity
- Large door opening for easy loading and unloading
  - extra strong hing and reversible door
- Galvanized drum - oval drum holes preventing damage from standard drywall screws
- Unique suspension system
  - at the rear: bearings
  - at the front: rubber rollers with bearings
- Large lint filter - easy removal of lint, efficient drying
- Axial airflow
  - drum perforations only at the front and back
  - maximum airflow, less energy consumption and short drying times
- Average of 40% lower energy input compared with Speed Queen classic tumblers
- Overall utility savings per year are around 5%
- Quantum™ Gold Controls
  - easy to operate
  - flexibility of 5 programmable cycles
- Single slot electronic multi denomination coin drop for versatility and accuracy
- Digital display and countdown

### Options


- Electric and Steam heat
- LPG Conversion
- Stainless steel front and tumbler cylinder
- Quantum Network Control Card (NK301)
- ECO Energy saver models



LOW ENERGY CONSUMPTION




LARGE DOOR OPENING



HIGH OUTPUT



EASY OPERATION



STACK UNIT



NETWORK CAPABLE



Quantum™ Gold Control

### Quantum™ Gold Controls

In addition to its network capabilities and remote off-site management features, Quantum™ Gold offers additional owner and customer benefits such as PC programming and machine audit capabilities, as well as time-of-day pricing, a "lucky cycle" for loyal customers and the ability to interface with the store owner's payment systems. Cycle modifier keys create additional profit opportunities for store owners.



|                                    | <b>STT30</b>                               | <b>STT45</b>                                   |
|------------------------------------|--|--|
| <b>Drum</b>                        |  |  |
| Capacity 20:1 kg                   | 14kg                                       | 21kg   |
| Volume l                           | 301Lt                                      | 421Lt  |
| Cylinder diameter mm               | 762mm                                      | 838mm  |
| <b>Programmer</b>                  |  |  |
| Type of control                    | Quantum Gold                               | Quantum Gold                                   |
| <b>Cabinet</b>                     |  |  |
| Colour                             | White, option stainless steel              | White, option stainless steel                  |
| Drum                               | Galvanized, option stainless steel         | Galvanized, option stainless steel             |
| Dryer door handle                  | Black plastic                              | Black plastic                                  |
| <b>Heating</b>                     |  |  |
| Gas                                | 77MJ/hr per pocket (154MJ/hr both pockets) | 91.8MJ/hr per pocket (183.6MJ/hr both pockets) |
| Electric                           | 12 kW                                      | n/a  |
| <b>Connection</b>                  |  |  |
| Gas and Steam                      | Non Rev Amps (both pockets)                | Non Rev Amps (both pockets)                    |
| 240V/50HZ/1 2W+G                   | 9.0 total                                  | 10.8 total                                     |
| Full Load Amps                     | 9.0  | 10.8   |
| Make Up Air Supply                 | 1418cm <sup>2</sup>                        | 1856cm <sup>2</sup>                            |
| Air Outlet diameter mm             | 200mm                                      | 250mm  |
| Gas Inlet (NPT)                    | 12mm                                       | 12mm   |
| <b>Operation</b>                   |  |  |
| Drying Cycles                      | 5  | 5  |
| Motor Horsepower (Fan kW/Drive kW) | 0.19 / 0.19                                | 0.37 / 0.37                                    |
| Decibel rating                     | 66dBA                                      | 67dBA  |
| <b>Transport Data</b>              |  |  |
| Gross Weight                       | 264kg                                      | 326kg  |
| Net Weight                         | 247kg                                      | 305kg  |
| Dimensions HxWxD                   | 1937 x 800 x 1086mm                        | 2059x876x1235mm                                |
| Packaging dimensions HxWxD         | 2057 x 825 x 1194mm                        | 2159 x 902 x 1372mm                            |
| Volume m <sup>3</sup>              | 2.0m <sup>3</sup>                          | 2.7m <sup>3</sup>                              |
| <b>Agency Approvals</b>            |  |  |
| Australian gas approval            | #7430                                      | #7430  |
| CE approval                        | Yes  | Yes  |



White Panels



Stainless Steel Front



## Dimensions

|              | A   | B    | C    | D   | E   | F   | G     | H   | I     | J      |
|--------------|-----|------|------|-----|-----|-----|-------|-----|-------|--------|
| <b>STT30</b> | 711 | 1245 | 1226 | 290 | 272 | 636 | 1086  | 695 | 800   | 1937   |
| <b>STT45</b> | 810 | 1280 | 1252 | 262 | 236 | 746 | 1235  | 775 | 876   | 2059   |
|              |     |      |      |     |     |     | depth |     | width | height |

All measurements are in mm.

