



10 KG - PUSH TO START MANUALLY OPERATED GAS DRYER

Features and Benefits

- Durable, easy to use controls for low maintenance costs, well suited to high volume multiple operator applications.
- 100% front service dryer reduces maintenance time and costs ensuring maximum availability.
- Rear controls matching the SWNMN2 top load washer for perfect paring of both capacity and style.
- Super robust steel control consol well suited to heavy handed operators.

SPECIFICATIONS

DIMENSIONS	
CAPACITY	10 kg
WIDTH	683 mm
DEPTH	711 mm
HEIGHT	1,114 mm
DRUM VOLUME	198 litres
NET WEIGHT	61 kg
OPERATION	
CYCLES	4 cycles, 3 fabric temperatures
CYCLE INDICATOR	Yes
CYCLE TIME	20-60 min
CONTROLS	Single button push to start
ACTIVATION	Manual
HEAT INPUT	27Mj Natural Gas or LPG
MOTOR	1/3 hp
POWER SUPPLY	10 amp single phase
CONSTRUCTION	
DRUM	Galvanised steel
OUTER CABINET	Steel



SDGMNR Commercial Dryer

TECHNICAL SPECIFICATIONS

UTILITIES
SINGLE PHASE 240 V 50 HZ 10 AMP
10 AMP CIRCUIT-BREAKER REQUIRED
1.8 M POWER CORD
FLUE DIAMETER 102 MM (4 IN)
AIR FLOW 85 LITERS / SEC
GAS SUPPLY CONNECTIONS 3/8"NPT (9.5MM)
OPTIONAL RIGHT OR LEFT SIDE VENTING

*For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications are subject to change without notice.

SHIPPING DIMENSIONS	
WEIGHT	66 kg
HEIGHT	1,156 mm
WIDTH	737 mm
DEPTH	832 mm, 0.71 m³

CONTROL

