



10 KG - PUSH TO START MANUALLY OPERATED STACKED GAS DRYER

Features and Benefits

- Durable, easy to use controls for low maintenance costs, well suited to high volume multiple operator applications.
- 100% front service dryers reduce maintenance time and costs ensuring maximum availability.
- Stacked dryers maximising space utilisation.
- Super robust steel control console well suited to heavy handed operators.

SPECIFICATIONS

DIMENSIONS	
CAPACITY	10 kg (x2)
WIDTH	683 mm
DEPTH	711 mm
HEIGHT	1,986 mm
DRUM VOLUME	198 litres (x2)
NET WEIGHT	120 kg
OPERATION	
CYCLES	4 cycles, 3 fabric temperatures
CYCLE INDICATOR	Yes
CYCLE TIME	20-60 min
CONTROLS	Push to start
ACTIVATION	Manual
ENERGY INPUT	27.4 mj (x2) LPG or natural gas
MOTOR	1/3 hp
POWER SUPPLY	10 amp (x2) single phase
CONSTRUCTION	
DRUM	Galvanised
OUTER CABINET	Steel



SSGMNA Stacked Commercial Dryer

TECHNICAL SPECIFICATIONS

UTILITIES
2 X 10 AMP SINGLE PHASE 240 V 50 HZ
2 X 10 AMP CIRCUIT-BREAKER REQUIRED
2 X 1.8 M POWER CORDS
2 X FLUE DIAMETER 102 MM (4 IN)
2 X AIR FLOW 85 LITERS / SEC
2 X MAX POWER DRAW 350 W / HR
X2 GAS SUPPLY CONNECTIONS 3/8 INCH NPT
X2 GAS CONSUMPTION 26 MJ / HR
OPTIONAL RIGHT OR LEFT SIDE VENTING

SHIPPING DIMENSIONS	
WEIGHT	127 kg
HEIGHT	2,032 mm
WIDTH	838 mm
DEPTH	762 mm
	1.29 m ³

