

# STENXA Commercial Washer/Dryer



## 10 KG FRONT LOAD WASHER AND ELECTRIC DRYER

### Features and Benefits

- Payment options available - Coin, Token, Credit card and Payment App.
- Low water consumption of only 44.3 litres per wash, with full wash completed in 30 minutes.
- Energy saving 'High Speed Extract' spin cycle of 1,200 rpm producing 'G' forces in excess of 440 for greater water removal, resulting in reduced drying times and associated energy savings.
- 100% front service dryer.
- Touch push button controls robust and easy to use controls suitable for high volume multiple operator applications.

### SPECIFICATIONS

DIMENSIONS	
CAPACITY	10 kg washer, 10 kg dryer
WIDTH	683 mm
DEPTH	796 mm
HEIGHT	1,986 mm
NET WEIGHT	177 kg
OPERATION	
CYCLES	9 cycles, 3 soil levels
CYCLE LIGHTS	Yes
CYCLE TIME	26 - 30 minutes
CONTROLS	Touch push button controls
ACTIVATION	Coin, Token, Card or Payment App
WATER TEMPERATURE	Cold, Warm or Hot
MOTOR WASHER SPIN	1 hp, variable speed
SPEED WASHER	500 - 1,200 rpm, variable
WATER USE WASHER	speed 44.3 litres / wash
HEAT INPUT DRYER	4,000 w
CONSTRUCTION	
INNER BOWL WASHER	Stainless steel
OUTER BOWL WASHER	Stainless steel
OUTER CABINET	Steel
DRUM DRYER	Galvanised



# STENXA Commercial Washer/Dryer

## TECHNICAL SPECIFICATIONS

UTILITIES WASHER
10 AMP SINGLE PHASE 240 V 50 HZ
10 AMP CIRCUIT-BREAKER REQUIRED
1.8 M POWER CORD
HOT AND COLD WATER CONNECTIONS REQUIRED
1.2 M HOT AND COLD WATER HOSES SUPPLIED
WATER SUPPLY HOSE TAP ENDS 3/4 BSP THREADS
MAX HOT WATER CONSUMPTION 18.7 LITRE / CYCLE
MAX WATER CONSUMPTION 44.3 LITRE / CYCLE
MAX POWER DRAW 750 W / HR
DRAIN: 610 - 914 MM UPSTAND, 50 MM DIAMETER
WATER SUPPLY PRESSURE BETWEEN 140 - 820 KPA

UTILITIES DRYER	
20 AMP SINGLE PHASE	240 V 50 Hz
20 AMP	Circuit breaker required
1.8 M	Power Cord
FLUE DIAMETER	102 mm (4 in)
AIR FLOW	85 litres / second
MAX POWER DRAW	4,000 w / hour
OPTIONAL	Right or left side venting
SHIPPING DIMENSIONS	
WEIGHT	189 kg
HEIGHT	2,032 mm
WIDTH	762 mm
DEPTH	864 mm
	1.33 m <sup>3</sup>

- A: 1,678\* mm

E: 610 mm

I: 368\* mm

M: 1,148\* mm)
- B: 1,447\* mm

F: 203 mm

J: 813\* mm

N: 52 mm
- C: 597 mm

G: 391 mm

K: 683 mm

O: 704 mm
- D: 213 mm

H: 938\* mm

L: 1,986\* mm

\* With Leveling Legs Turned Into Base.

